

# **Safety Data Sheet**

# Isopropyl Alcohol, USP

# 1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: Isopropyl Alcohol, USP

Synonyms/Generic Names: IPA, Isopropanol, 2-propanol, sec-Propyl alcohol

**Product Number: 2870** 

Product Use: Industrial, Manufacturing or Laboratory use

Manufacturer: Columbus Chemical Industries, Inc.

N4335 Temkin Rd. Columbus, WI. 53925

For More Information Call: 920-623-2140 (Monday-Friday 8:00-4:30)

In Case of Emergency Call: CHEMTREC - 800-424-9300 or 703-527-3887 (24 Hours/Day, 7 Days/Week)

# 2. HAZARDS IDENTIFICATION

OSHA Hazards: Flammable liquid, Target organ effect, Irritant

Target Organs: Nerves, Kidneys, Cardiovascular system, Gastrointestinal tract, Liver

Signal Word: Danger

**Pictograms:** 



#### **GHS Classification:**

Flammable liquids	Category 2
Skin irritation	Category 3
Eye irritation	Category 2A
Specific target organ toxicity-single exposure	Category 3

## **GHS Label Elements, including precautionary statements:**

#### **Hazard Statements:**

H225	Highly flammable liquid and vapor		
H316	Causes mild skin irritation.		
H319	Causes serious eye irritation.		
H336	May cause drowsiness or dizziness.		

Revised on 01/14/2015 Page 1 of 6

**Precautionary Statements:** 

reductionary otatements.				
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.			
P233	Keep container tightly closed.			
P240	Ground/Bond container and receiving equipment.			
P241	Use explosion-proof electrical/ventilating/lighting/equipment.			
P242	Use only non-sparking tools.			
P243	Take precautionary measures against static discharge.			
P261	Avoid breathing dust/fume/gas/mist/vapors/spray.			
P264	Wash hands thoroughly after handling.			
P271	Use only outdoors or in a well-ventilated area.			
P280	Wear protective gloves/protective clothing/eye protection/face protection.			
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse			
	skin with water/shower.			
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.			
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact			
	lenses, if present and easy to do. Continue rinsing.			
P312	Call a POISON CENTER/doctor/physician if you feel unwell.			
P332+P313	If skin irritation occurs: Get medical advice/attention.			
P337+P313	If eye irritation persists: Get medical advice/attention.			
P370+P378	In case of fire: Use appropriate media to extinguish.			
P403+P233	Store in a well-ventilated place. Keep container tightly closed.			
P405	Store locked up.			
P501	Dispose of contents/container in accordance with local regulations.			

# **Potential Health Effects**

Eyes	Causes eye irritation.
Inhalation	May be harmful if inhaled. Causes respiratory tract irritation. Vapors may cause drowsiness and dizziness. Can cause irritation of mucous membranes and central nervous system depression.
Skin	May be harmful if absorbed through skin. Causes skin irritation.
Ingestion	May be harmful if swallowed.

**NFPA Ratings** 

Health	1	
Flammability	3	
Reactivity	1	
Specific hazard	Not Available	

**HMIS Ratings** 

Health	2
Fire	3
Reactivity	0
Personal	Н

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Weight %	CAS#	EINECS# / ELINCS#	Formula	Molecular Weight
Isopropyl Alcohol	>99	67-63-0	200-661-7	C <sub>3</sub> H <sub>8</sub> O	60.10 g/mol

# 4. FIRST-AID MEASURES

Eyes	Rinse with plenty of water for at least 15 minutes and seek medical attention.
Inhalation	Move casualty to fresh air and keep at rest. If breathing is difficult, give oxygen. If not
	breathing, give artificial respiration. Get medical attention.
Skin	Flush with plenty of water for at least 15 minutes while removing contaminated clothing and
	wash using soap. Get medical attention.
Ingestion	Do Not Induce Vomiting! Never give anything by mouth to an unconscious person. If
	conscious, wash out mouth with water. Get medical attention.

Revised on 01/14/2015 Page 2 of 6

## 5. FIREFIGHTING MEASURES

Suitable (and unsuitable)	Flammable in the presence of a source of ignition when the temperature			
extinguishing media	is above the flash point. Use water spray, alcohol-resistant foam, dry			
	chemical or carbon dioxide. Use appropriate media for adjacent fire.			
	Cool containers with water.			
Special protective equipment	Wear self-contained, approved breathing apparatus and full protective			
and precautions for firefighters	clothing, including eye protection and boots. Use water spray to cool			
	fire-exposed containers and disperse vapors. Containers may rupture in			
	the heat of the fire. Do not use direct water stream, may spread the fire.			
Specific hazards arising from	Emits toxic fumes (carbon oxides) under fire conditions.			
the chemical	Vapors can travel to a source of ignition and flash back. Containers may			
	explode in a fire. Cool containers from a distance using water spray.			
	Flames may be invisible. (See also Stability and Reactivity section)			

## 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	See section 8 for recommendations on the use of personal protective equipment.		
Environmental precautions	Do not let product enter drains. Any release to the environment may be		
	subject to federal/national or local reporting requirements.		
Methods and materials for	Absorb spill with vermiculite or other noncombustible absorbent material,		
containment and cleaning up	then place in a suitable container for disposal. Clean surfaces thoroughly		
	with water to remove residual contamination. Dispose of all waste and		
	cleanup materials in accordance with local regulations.		

# 7. HANDLING AND STORAGE

#### Precautions for safe handling

Use with adequate ventilation and grounding. Wash thoroughly after using. Keep container closed when not in use. See section 8 for recommendations on the use of personal protective equipment. Avoid contact with skin and eyes. Avoid inhalation of vapor or mist. Use explosion-proof equipment. Take measure to prevent the buildup of electrostatic charge.

# Conditions for safe storage, including any incompatibilities

Store in tightly closed, original containers in a cool, dry, well ventilated area. Do not store with strong oxidizing agents, strong acids, peroxides, aldehydes, halogens, ammonia, acid anhydrides or alkali metals. Keep away from incompatible materials (see section 10 for incompatibilities).

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Occupational exposure controls: Appropriate grounding of containers.

Component	Exposure Limits	Basis	Entity
Isopropyl Alcohol	200 ppm 492 mg/m <sup>3</sup>	TLV	ACGIH
	400 ppm 984 mg/m <sup>3</sup>	STEL	ACGIH
	400 ppm 980 mg/m <sup>3</sup>	PEL	OSHA
	2000 ppm	IDLH	OSHA

Revised on 01/14/2015 Page 3 of 6

400 ppm 980 mg/m <sup>3</sup>	REL	NIOSH
500 ppm 1225 mg/m <sup>3</sup>	STEL	NIOSH

TWA: Time Weighted Average over 8 hours of work. TLV: Threshold Limit Value over 8 hours of work.

REL: Recommended Exposure Limit PEL: Permissible Exposure Limit

STEL: Short Term Exposure Limit during x minutes. IDLH: Immediately Dangerous to Life or Health WEEL: Workplace Environmental Exposure Levels

**CEIL: Ceiling** 

#### **Personal Protection**

Eyes	Wear chemical safety glasses or goggles, and face shield.
Inhalation	Provide local exhaust, preferably mechanical. If exposure levels are excessive, use an approved respirator.
Skin	Wear nitrile or rubber gloves, and full body covering. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.
Other	Not Available

#### **Other Recommendations**

Provide eyewash stations, quick-drench showers and washing facilities accessible to areas of use and handling. Have supplies and equipment for neutralization and running water available.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance (physical state, color, etc.)	Clear, colorless liquid
Odor	Mild alcohol
Odor threshold	Not Available
pH	Not Available
Melting point/freezing point	-89°C (-129°F)
Initial boiling point and boiling range	82°C (180°F)
Flash point	12°C (54°F)
Evaporation rate	3.0
Flammability (solid, gas)	Flammable
Upper/lower flammability or explosive limit	LEL: 2.5% UEL:12%
Vapor pressure	33 mmHg (@ 20°C)
Vapor density	2.07 (air=1)
Relative density	Not Available
Solubility (ies)	Completely soluble in water
Partition coefficient: n-octanol/water	Log Pow: 0.05
Auto-ignition temperature	399°C (750°F)
Decomposition temperature	Not Available

## 10. STABILITY AND REACTIVITY

Chemical Stability	Stable
Possibility of Hazardous Reactions	Will not occur.
Conditions to Avoid	Keep away from heat, flame and sparks
Incompatible Materials	Acids, alkali metals, oxidizing agents, iron salts, potassium,
	aluminum. May attack plastics and rubber.
Hazardous Decomposition Products	Carbon oxides.

Revised on 01/14/2015 Page 4 of 6

# 11. TOXICOLOGICAL INFORMATION

# Acute Toxicity Isopropanol

Skin	LD50 – rabbit – 18,286 mg/kg	
Eyes	Not Available	
Respiratory	Not Available	
Ingestion	LD50 – mouse – 5,143 mg/kg	

Carcinogenicity

IARC	3-Group 3: Not classifiable as to its carcinogenicity to humans (Isopropyl Alcohol).
ACGIH	A4: Not classifiable as a human carcinogen (Isopropyl Alcohol).
NTP	No components of this product present at levels greater than or equal to 0.1% is identified
	as a known or anticipated carcinogen by NTP.
OSHA	No components of this product present at levels greater than or equal to 0.1% is identified
	as a carcinogen or potential carcinogen by OSHA.

Signs & Symptoms of Exposure

Skin	Burning, itching, redness. May be harmful if absorbed through skin.
Eyes	Redness, excessive blinking and watering eyes.
Respiratory	Coughing, wheezing, headache, disorientation, blurred vision, dizziness, fatigue or nausea.
Ingestion	Nausea, vomiting and central nervous system depression.

Chronic Toxicity	May cause damage to the following organs: kidneys, liver, skin, central
	nervous system.
Teratogenicity	Not Available
Mutagenicity	Not Available
Embryotoxicity	Pre- and Post- implant mortality.
Specific Target Organ Toxicity May cause drowsiness or dizziness.	
Reproductive Toxicity	Not Available
Respiratory/Skin Sensitization	Not Available

# 12. ECOLOGICAL INFORMATION

Isopropanol

Aquatic Vertebrate	Not Available
Aquatic Invertebrate	Not Available
Terrestrial	Not Available

Persistence and Degradability	Not Available
Bioaccumulative Potential	Not Available
Mobility in Soil	Not Available
PBT and vPvB Assessment	Not Available
Other Adverse Effects	Not Available

# 13. DISPOSAL CONSIDERATIONS

Waste Residues	Users should review their operations in terms of the applicable federal/national or local regulations and consult with appropriate regulatory agencies if necessary before disposing of waste product container or residue.	
Product	Users should review their operations in terms of the applicable federal/national or	
Containers	local regulations and consult with appropriate regulatory agencies if necessary	
	before disposing of waste product container.	

Page 5 of 6 Revised on 01/14/2015

The information offered in section 13 is for the product as shipped. Use and/or alterations to the product may significantly change the characteristics of the material and alter the waste classification and proper disposal methods.

# 14. TRANSPORTATION INFORMATION

US DOT	UN1219, Isopropanol, 3, pg II
TDG	UN1219, ISOPROPANOL, 3, pg II
IMDG	UN1219, ISOPROPANOL, 3, pg II
Marine Pollutant	No
IATA/ICAO	UN1219, Isopropanol, 3, pg II

# 15. REGULATORY INFORMATION

TSCA Inventory Status	All ingredients are listed on the TSCA inventory.
DSCL (EEC)	All ingredients are listed on the DSCL inventory.
California Proposition 65	Not Listed
SARA 302	No SARA Hazard
SARA 304	No SARA Hazard
SARA 311	Fire Hazard, Acute Health Hazard, Chronic Health Hazard
SARA 312	Fire Hazard, Acute Health Hazard, Chronic Health Hazard
SARA 313	No SARA Hazard
WHMIS Canada	Class B-2: Flammable and combustible liquid- Flammable liquid
	Class D-2B: Poisonous and infectious material- Other effects- Toxic

# 16. OTHER INFORMATION

Revision	Date
Revision 1	07-13-2011
Revision 2	10/17/2013
Revision 3	01/14/2015

Disclaimer: Columbus Chemical Industries, Inc. ("Columbus") believes that the information herein is factual but is not intended to be all inclusive. The information relates only to the specific material designated and does not relate to its use in combination with other materials or its use as to any particular process. Because safety standards and regulations are subject to change and because Columbus has no continuing control over the material, those handling, storing or using the material should satisfy themselves that they have current information regarding the particular way the material is handled, stored or used and that the same is done in accordance with federal, state and local law. COLUMBUS MAKES NO WARRANTY, EXPRESS OR IMPLIED, INCLUDING (WITHOUT LIMITATION) WARRANTIES WITH RESPECT TO THE COMPLETENESS OR CONTINUING ACCURACY OF THE INFORMATION CONTAINED HEREIN OR WITH RESPECT TO FITNESS FOR ANY PARTICULAR USE.

Revised on 01/14/2015 Page 6 of 6